Profiles Advanced tab

Overview

Use this tab to specify a Tiki repository URL and data channel

Related Topics

• Tiki Profiles

To Access

From the Profiles Admin page, click the **Advanced** tab.

| Option | Description | Default |
|--|--|-----------------------------|
| Automatically approve wikiplugins on pages installed by profiles | Some wiki-plugins require admin approval before they are executable. If turned on, then all wiki-plugins that are on wiki pages created via profiles are automatically approved. • Make sure your profiles are not executable or editable by untrusted users. | Disabled |
| Developer mode | For profiles under an approval workflow, always use the latest version, even if not approved. • Make sure you review the profiles you install. | Disabled |
| Repository URLs | List of URLs for the profile repositories that will be used be Enter multiple repository URLs, one per line. | http://profiles.tiki.org/pr |
| Data channels | Data channels are templates that can be applied from a post request. They can be used to automate work on more complex installations. Data channels create a named pipe to run profiles from user space. One channel per line. Each line is comma delimited and contains channel name, domain, profile, allowed groups, (optional) \$profilerequest:input\$ matches to groups. There are security considerations related to using data channels. Make sure the profile page is controlled by administrators only. | None |

| Option | Description | Default |
|--|--|-----------------------------|
| Automatically approve wikiplugins on pages installed by profiles | Some wiki-plugins require admin approval before they are executable. If turned on, then all wiki-plugins that are on wiki pages created via profiles are automatically approved. • Make sure your profiles are not executable or editable by untrusted users. | Disabled |
| Developer mode | For profiles under an approval workflow, always use the latest version, even if not approved. • Make sure you review the profiles you install. | Disabled |
| Repository URLs | List of URLs for the profile repositories that will be used be Enter multiple repository URLs, one per line. | http://profiles.tiki.org/pr |
| Data channels | Data channels are templates that can be applied from a post request. They can be used to automate work on more complex installations. Data channels create a named pipe to run profiles from user space. One channel per line. Each line is comma delimited and contains channel name, domain, profile, allowed groups, (optional) \$profilerequest:input\$ matches to groups. There are security considerations related to using data channels. Make sure the profile page is controlled by administrators only. | None |

| Option | Description | Default |
|--|--|-----------------------------|
| Automatically approve wiki- plugins on pages installed by profiles | Some wiki-plugins require admin approval before they are executable. If turned on, then all wiki-plugins that are on wiki pages created via profiles are automatically approved. • Make sure your profiles are not executable or editable by untrusted users. | Disabled |
| Developer mode | For profiles under an approval workflow, always use the latest version, even if not approved. • Make sure you review the profiles you install. | Disabled |
| Repository URLs | List of URLs for the profile repositories that will be used be Enter multiple repository URLs, one per line. | http://profiles.tiki.org/pr |

| Option | Description | Default |
|---------------|--|---------|
| Data channels | Data channels are templates that can be applied from a post request. They can be used to automate work on more complex installations. Data channels create a named pipe to run profiles from user space. One channel per line. Each line is comma delimited and contains channel name, domain, profile, allowed groups, (optional) \$profilerequest:input\$ matches to groups. There are security considerations related to using data channels. Make sure the profile page is controlled by administrators only. | None |

| Option | Description | Default |
|--|--|-----------------------------|
| Automatically approve wikiplugins on pages installed by profiles | Some wiki-plugins require admin approval before they are executable. If turned on, then all wiki-plugins that are on wiki pages created via profiles are automatically approved. • Make sure your profiles are not executable or editable by untrusted users. | Disabled |
| Developer mode | For profiles under an approval workflow, always use the latest version, even if not approved. • Make sure you review the profiles you install. | Disabled |
| Repository URLs | List of URLs for the profile repositories that will be used be Enter multiple repository URLs, one per line. | http://profiles.tiki.org/pr |
| Data channels | Data channels are templates that can be applied from a post request. They can be used to automate work on more complex installations. Data channels create a named pipe to run profiles from user space. One channel per line. Each line is comma delimited and contains channel name, domain, profile, allowed groups, (optional) \$profilerequest:input\$ matches to groups. There are security considerations related to using data channels. Make sure the profile page is controlled by administrators only. | None |

| Option | Description | Default |
|--|---|-----------------------------|
| Automatically approve wikiplugins on pages installed by profiles | Some wiki-plugins require admin approval before they are executable. If turned on, then all wiki-plugins that are on wiki pages created via profiles are automatically approved. • Make sure your profiles are not executable or editable by untrusted users. | Disabled |
| Developer mode | For profiles under an approval workflow, always use the latest version, even if not approved. • Make sure you review the profiles you install. | Disabled |
| Repository URLs | List of URLs for the profile repositories that will be used be Enter multiple repository URLs, one per line. | http://profiles.tiki.org/pr |
| Data channels | Data channels are templates that can be applied from a post request. They can be used to automate work on more complex installations. Data channels create a named pipe to run profiles from user space. One channel per line. Each line is comma delimited and contains channel name, domain, profile, allowed groups, (optional) \$profilerequest:input\$ matches to groups. There are security considerations related to using data channels. Make sure the profile page is controlled by administrators only. | None |