

<œiŠxí...œ êµ¬ì,,±

í<°í,x8 ì¬ì,,œ ë,,ìž...ë"

œiŠxí...œ êµ¬ì,,±íœ ì<œiŠxí...œ ê´œë¬¬ìžëíœ í°¬¬¬ê,^ í<°í,xì° ì™,ë¶¶ëì¬ì,,œ ì,, í° ì,,xì • ì¼ë¶¶ë¼ë¼ ë³œë²½í°~ë,,ëi í° ©ë<^ë<x. INI íœœì¼ì,,
œê³µí°¬ìœ¼ëiœè", ê´œë¬¬ìžë"œíœ ìžì< ë"œì° ë³"ë" í<°í,x ì,,xì¹¬ì— ëœœí°¬¬¬ìœ´ì<¬ êµ¬ì,,±ì,, ë³´ìœ í° ì°¬ìž°ìšµë<^ë<x.

í<°í,x10 ì¬ì,,œ ìf^ëíœ ë,,ìž...ëœ ë,´ìš©: ì • ì íœœì¼ìœë¶¶í,,° ë³"ë"¬ì,, ëíœë"œí°~ëš" ì,, ìfì,¬í° (í"„ëiœí°„, YAML í°¬ì<ë,´ì¬ì,,œ,
http://profiles.tiki.org/Module+Handler ì™€ ìœ ì,¬í°~ê²œ). ê´œë¬¬ìœë,, ë,´ë¶¶ëì¬ì,,œ "ë³"ë"¬ìœœì¼" ì,, ê²ë¶¶%í°¬ì<œèì°œ.

í<°í,x11 ì¬ì,,œ ìf^ëíœ ë,,ìž...ëœ ë,´ìš©: db/preconfiguration.php íœœì¼ìœ ì²<< í<°í,x ì,,xì¹¬ìœè¬ ìœè^ëœ ë°ì´í,,°ë² ì´ìšx ë³´ì°^ë,´ìš©ì,, í¬í°¬í° ì°¬
¬ìšµë<^ë<x. ì´ëš" ê°ë¶ì ì,,œë²,, ìœê³µìžëíœ í°¬¬¬ê,^ ê³ ê°ì´ í<°í,x ì,,xì¹¬ì"„ëíœë,ëž"ì¬ ì´ê¼í°~ê,° ì,,ì¬ mysql ì,, ê°ê,° ë<xœ¥, ìž,,ì°¬ ë¹,,ë°ëë²^í° ì™€
¬ìš©ìžë³...ìœ¼ëíœ ì,¬ì,,xì • í° ì°¬ìž^ë,,ëi í° ©ë<^ë<x.

<°í,x íœœ(farm)ê³¼ í° ìšxíœ... íšœì,¬ì¬ì,,œ ,¬ìš©ê°œëš¥í°œÅ ìš©ë²•

- BigBlueButton ê³¼ ê°™ìœ ë<xœ¥, ì,,œë¹,,ìšxëíœ ì,¬ìš©ìžì° ê°,,ì,,ì¬¬ì´ ì¬ê²°
- ë©xì°ì<œè™€ ê°™ìœ ê³ ê,°o ì,,xì •ì,, êµ¬ì,,±
- ìšœì> ê³,,ìšì ì¼ë¶¶ë°œ ì°„ë<œ ê,°ëš¥ì,, ë¹,,í™œèì,,±í™"
- ì,,ì¬ì ìœ¼ëíœ íš¹ì • ê,°ëš¥ì,, ë¹,,í™œèì,,±í™"í°¬ìœ¼ëíœè" ë³´ì°^ ì±...ìž,,ìžì¬ê²œ ìœœèì¼
- tiki_p_admin ì,, ìœê³µí°¬ìšœëšœ ì¼ë¶¶ë ê,°ëš¥ì,, ì´ê¼í°~ê,°œëš¥í°~ê²œ ëšœë"¬
- í° ìšxíœ... íšœì,¬ëš" ë³"ë" ê,°ëš¥ì,, í°œ ê³³¬ ìf´ìž¬í°œ í° ìœèì<ì,, ìœê³µí°~ê,°ë¼¼ ì>í° ì°¬ìž°ìšœëšœ, ë<xìœèì ì,¬ìš©ìœ ìœí°œí° ì°¬ìž^ë<x
 - ì<xí¬¬ì ê,°ëš¥
 - ì,,œë²,, ì´ê¼ì,, ì¬»ê,° ìœ,,í°¬¬¬ì,¬ìš©ë ì°¬ìž^ëš" ê,°ëš¥ (ëœœë¶¶ë¶¶,ì° ì,,xì¹¬ì¬ì,,œëš" ê´œè°@ìšœëšœ, ìœ,,í,xíœœ(WikiFarm)ì¬ì,,œëš" ì<ìœ ì¼ì ì°„ë<^ë<x)
- ì»¬ì,,xíœ... íšœì,¬ëš" ì,¬ìš©ìžì¬ ëœœí°¬¬¬ìœ" ë<¬ìœí°œ ê´œë¬¬ìœë,, ì,, ëšœë"œê³ ìœ¶ì-´í° ê²fì´ë<x
- í<°í,xë¼¼ ì´ìš© í"„ëíœê,ëž" ë¹œë" (í"„ë ìž,,ì>œí¬) ëíœèì ì,¬ìš©

<œïšœí...œ êµ¬ì,,±ì,,Â í™ œì,,±í™ ”

œïšœí...œ êµ¬ì,,±ì db/local.php íœœì¼œïœœ¶œí,,° í™ œì,,±í™ ”ë¬-î¼œšœ í•©ë^ë<œ. í<°í,œ8 ë° ê. í >,,ì-ì,,œ ìfi,,±ëœ ì,,œì¹~ëš” ê,°ë³,ìœ¼œïœ ìfi,,±ëœ
œœì¼ ë,´ë¶œì- ìf”í”œì,, í-í•í•ê³ ìž^ìšµë<^ë<œ.

db/local.php ë,´ë¶œì~ ìf”í”œ êµ¬ì,,±

```
$system_configuration_file = '/etc/tiki.ini'; $system_configuration_identifer = 'client1.example.com';
```

db/local.php ë,´ë¶œì~ ë<œëœ, ìf”í”œ êµ¬ì,,±, ìfëœë ê²¼ëïœëœ¼ í-í•

```
$system_configuration_file = 'db/tiki.ini'; $system_configuration_identifer = 'client1.example.com';
```

ì~^ì œëœ¼ ì,-ìšœí•ê²œ ë~ë©´ .htaccess ê°œ í™ œì,,±í™ ”ë¬-ìž^ì-ì,,œ tiki.ini ê°œ ì¼ìž^ìšœ ì•šë,,ëì í•~ëš” ê²fi- ìœ ìí•ì<œìœ

œì,,±í™ ”ë~ë©´, í<°í,œëš” êµ¬ì,,± íœœì¼œïœœ¶œí,,° ì,, ìfëœ ì<ë³,ìžì- ê,°ë~í•~ì- ì¶”ê°œ ëœ...ë ì,, ì½ì-´ë“œì¼ ê²fiž...ë<^ë<œ. ì<ë³,ìžëš” ìž,,ì~ì ê²fi¼ ì~
ìšœëšœ, ì,-ìíš, í~ìœ ê³,ìš ìœ í•~ë,~ëœ¼ ìšœì •í•ê³,° ìœ,,í•~ì- ì,-ìšœ ì~ ìž^ìšµë<^ë<œ. êµ¬ì,,± íœœì¼ ë,´ë¶œì-ëš” ë<œìœ’ êµ¬ì,,± ìí•ë ì~
ìœ¼ë° ìfiìì ì,-ìšœ ì~ ìž^ìšµë<^ë<œ.

Ni êµ¬ì,,±Â íœœì¼

ìf”í”œ INI íœœì¼

```
[global] preference.feature_wysiwyg = "n" preference.feature_sefurl = "y" preference.helpurl = "http://support.example.com/" ; ... more settings ...
[basic : global] preference.feature_wiki = "y" preference.feature_forums = "n" preference.feature_trackers = "n" ; ... more settings ... [pro : global]
preference.feature_wiki = "y" ; BBB configured, but user can still toggle on/off preference.bigbluebutton_server_location = "bbb.example.com"
preference.bigbluebutton_server_salt = "1234abcd1234abcd" ; ... more settings ... [client1.example.com : pro] preference.browsertitle = "Client #1
Intranet" preference.sender_email = client1@example.com
```

the example above, the following preferences would be set for using the identifier *client1.example.com*:

- feature_wysiwyg = n
- feature_sefurl = y
- helpurl = <http://support.example.com/>

- feature_wiki = y
- bigbluebutton_server_location = bbb.example.com
- bigbluebutton_server_salt = 1234abcd1234abcd
- browsertitle = Client #1 Intranet
- sender_email = [client1 at example.com](#)

at the beginning indicates comments

Disable classes of preferences

Preferences can be disabled by setting a value to each of them individually. However, this process may be long and will require maintenance with the evolutions of Tiki.

Tiki allows to set multiple rule priorities, each verification priority can allow or deny a preference. Rules can be specified at various levels, just like the preference overrides above.

Various rules

[global] rules.0 = deny experimental new [pro : global] rules.5 = allow new rules.10 = allow feature_wysiwyg

... [global] rules.0 = deny experimental new [pro : global] rules.5 = allow new rules.10 = allow feature_wysiwyg ...

... [pro : global] rules.5 = allow new rules.10 = allow feature_wysiwyg ...

Draconian rules

[global] rules.0 = deny all rules.1 = allow basic

... [global] rules.0 = deny all rules.1 = allow basic ...

, -ì „êµ¬ì,, ± íĀĀĒì¼

í,æ°€ ì,¬ì „, ëiœë“œëœ ì“ë”“ë©~ë“œ (on-demand)ìì~ ê°€ìf ë”_ì< ì,, ì œê³µí• ë•ĀĒ, í”_ìšxíĀĒ... íšĀĒì,¬ë“xì€ ê° ì,¬ìš©ìžì—ê²ĀĒ ë<xëŸ, ë°ì´í,,°ë² ì´ìšxì™€

-°ê²° ë³´í•^ë,´ì—ìœ¼œiœ mysql ì,, ì œê³µí• ì~ ìž^ë<x.
xì¹~ ´”„ëiœê•_ëž“ì~ ë°ì´í,,°ë² ì´ìšx ì—°ê²° ì,,xì • ë<“ê³,,ì— ì ‘ê•¼í• ë•ĀĒ, ì‘ëŸ¬í•œ ê°‘ë“xì€ ì,¬ìš©ìžëŸ¼ ìœ,,í•~ì—¬ ì,¬ì „ì— ê„°ž...ë ê²fì´ë”“ă... ì´ëš”

©”¼¼ í”¼ì€ ë<xëŸ, ë°©ì<ì,, ì´ìš©í•~ì—¬ ì œê³µí•~ëš” ê²fë³´ë<x ë” íš“ìœ“ì ì´ë<x.
ëŸ¬í•œ ì •ë³´ëš” ëŸ,,ëª...í•œ ì´ìœ ëiœ db/local.php ë,´ëŸì— í¬í•“ë ì~ ì—†ë<x ê•_ ì´ìœ ëš” local.php ê°€ ì´ ë<“ê³,,ì—ëš” ì•,,ìš ìì ìž¬í•~ìš€ ì•šê„°
•ĀĒ¬_ì´ë<x.

í•¼ë ê²fì€ ë<“ì^œíž^ db/preconfiguration.php ì— ì ì´í•œ ìx,,ì~ ì£¼ì,,ìfìfœëŸ¼ í•´ìš€í•~ëš” ê²fì´ê³ ì ì´í•œ ê°´ìœ¼œiœ ì±,,ìš°ëš” ê²fì´ë<x:

db/preconfiguration.php