

$$\tilde{A} \neg \hat{A}' \quad \tilde{A} \check{Z} \sim \tilde{A} \neg \hat{A}' \tilde{A} \neg \hat{A} \S \in \tilde{A} \neg \quad \tilde{A} \ll \hat{A}^2 \wedge \tilde{A} \neg \neg \hat{A} \tilde{A} \neg \in \tilde{A} \neg^{\text{TM}} \,, \tilde{A} \ll \hat{A} \not\subseteq \mathbb{E} \tilde{A} \ll \sim \tilde{A} \neg \hat{A} \S \in \tilde{A} \neg \cdot \check{S} \tilde{A} \neg \cdot \sim \tilde{A} \neg \hat{S} \hat{\mu} \tilde{A} \ll \langle \hat{A} \tilde{A} \ll \hat{A} \aleph.$$
$$\tilde{A} \neg \text{œ} , , \tilde{A} , \hat{A} \text{⌘} \tilde{A} \neg \hat{A} , \tilde{A} \neg ^{\sim} \tilde{A} \ll \hat{A}^3 \in \tilde{A} \neg ^{\sim}$$

$\tilde{A} \rightarrow \hat{A}'$   $\tilde{A} \rightarrow \hat{A}$   $\tilde{A} \ll \hat{A}^3 \hat{A} \odot \tilde{A} \rightarrow \in$   $\tilde{A} \langle \hat{A}^\circ \tilde{A}, \hat{A} \bowtie \tilde{A} \rightarrow - \tilde{A} \rightarrow,, \tilde{A} \rightarrow, \hat{A} \rightarrow \tilde{A} \rightarrow \hat{S} \hat{A} \odot \tilde{A} \ll \hat{A}$   $\tilde{A} \rightarrow \sim$   $\tilde{A} \rightarrow \hat{Z}^{\wedge} \tilde{A} \ll \hat{S}$ "  $\tilde{A} \rightarrow \hat{A}^{1/4} \tilde{A} \ll \hat{A} \P \in$   $\tilde{A} \ll \hat{A}^3 \in \tilde{A} \rightarrow \sim$   $\tilde{A} \ll \hat{A} \nmid \hat{A}^{1/4}$   $\tilde{A} \ll,, \tilde{A}$ -  
 $f \in \tilde{A} \ll f \dots \tilde{A} \ll \langle^{\wedge} \tilde{A} \ll \langle \hat{A} \bowtie, \tilde{A} \rightarrow \sim^{\wedge} \tilde{A} \ll \hat{A} \nmid \hat{A}^{1/4}$   $\tilde{A} \ll \text{"} \hat{A} \bowtie \tilde{A} \ll \hat{A} \odot \hat{A}'$  : user, page, itemId.  $\tilde{A}^3 \hat{A}^\circ,, \tilde{A} \ll \langle \hat{A} \tilde{A} \bullet \tilde{A} \rightarrow \hat{A}'$   $\tilde{A} \rightarrow \hat{A} \bowtie'$   $\tilde{A} \rightarrow \hat{A} \bowtie' \tilde{A}^3 \hat{A}'$  ,,  $\tilde{A} \sim \hat{A}, \tilde{A} \ll \hat{A}; \tilde{A} \rightarrow \in$   
 $\tilde{A} \rightarrow \in$ "  $\tilde{A} \rightarrow \bullet,, \tilde{A} \rightarrow,, \tilde{A} \rightarrow \in$  ,,  $\tilde{A}, \hat{A} \bowtie \tilde{A} \ll \hat{A} \rightarrow \hat{A}, \tilde{A} \ll \hat{A}^2 \bullet$  using double angle brackets around them, once this preference is enabled in "Admin > Editing & Plugins" panel, you can put them in your wiki syntax enabled text area and have them to become automatically replaced by their actual value anywhere where they are used.

# PERMANENT VARIABLES

(on a tracker item)  
 Ã-æ,Ã,Ã» Ã-Ã,Ã-^~ Ã«Ã³€Ã-^~ (on a wiki page)  
 4829 (id from a wiki page; added in Tiki 12.1)  
 (when a user is logged in)  
 copydoc.tiki.org (site domain; added in Tiki 12.1)  
 copydoc.tiki.org/ (site domain ending with a slash; added in Tiki 12.1)  
 (only when in a multitiki installation,  
 site domain ending with a slash;  
 if the page doesn't belong to a multitiki installation,  
 nothing is returned; added in Tiki 12.1)  
 2 (last version of the wiki page; added in Tiki 12.2)  
 Marc Laporte (last editor of the wiki page; added in Tiki 12.2)  
 Thu 18 Oct, 2018 14:19 GMT-0000 (last modification date, in short format,  
 of the wiki page; added in Tiki 12.2)  
 (last version of the tracker item  
 indicated in the url; added in Tiki 12.2)  
 (last editor of the tracker item  
 indicated in the url; added in Tiki 12.2)  
 (last modification date, in short format,  
 of the tracker item indicated in the url; added in Tiki 12.2)  
 (last approved version of the wiki page  
 when revision approval is on; added in Tiki 12.3)  
 (last approver of the wiki page  
 when revision approval is on; added in Tiki 12.3)  
 (last approval date, in short format, of the wiki page  
 when revision approval is on; added in Tiki 12.3)

# EXAMPLE

If you put this syntax on a page named "My Profile":

```
* #
* ~œ,,~,,~ ~-~,,~-^~ ~«~³€~-^~
*
* copydoc.tiki.org
* copydoc.tiki.org/
```

it will produce (assuming you're viewing the page logged in as user admin):

- #1
- My Profile
- admin
- doc.tiki.org
- doc.tiki.org/

## LIVE EXAMPLE

You are currently on the page id 4829 with the name "~œ,,~,,~ ~-~,,~-^~ ~«~³€~-^~". Check [wiki source!](#).  
Your name is .

# User defined variables

When this option is active, it is possible to show the value of variables passed by argument on the URL. Note that a default value can be provided.

# LIVE EXAMPLE

```
*'lalala' is:  
*'lalala' is:
```

Shows:

- *lalala* is:
- *lalala* is:

Follow the link to give a value to *lalala*: [tiki-index\\_raw.php?page=Wiki+Argument+Variables&lalala=trololo](http://tiki-index_raw.php?page=Wiki+Argument+Variables&lalala=trololo)