

Module last_tracker_items

This is a stub. Some screenshot is needed

Parameters

Displays the value of a field of the specified number of tracker items. If the specified tracker has no main field, either

Field name or Field identifier is required.

*Required parameters are in **bold**.*

[Go to the source code](#)

Preferences required: feature_trackers

Parameters	Accepted Values	Description	Default	Since
trackerId	int	Identifier of the tracker from which items are listed. Example value: 13.		
name	any string except for HTML and PHP tags	Name of the field from which values are listed. Example value: age.		
sort_mode	any string except for HTML and PHP tags	Specifies how the items should be sorted. Possible values include created and created_asc (equivalent), created_desc, status, lastModif, createdBy and lastModifBy. Unless "_desc" is specified, the sort is ascending. "created" sorts on item creation date. "lastModif" sorts on the last modification date of items. "lastModif_desc" sorts in descending order of last modification date. Default value: created_desc		
status	word	If set, limits the listed items to those with the given statuses. Values are combinations of "o" (open), "p" (pending) and "c" (closed). Possible values: opc, oc, op, pc, o, p or c. Default value: opc		
fieldId	int	Identifier of the field from which values are listed. If Field name is set, this parameter is ignored. Example value: 13.		

The other traditional modules params apply:

Notes

- In $tw \geq 3.0$, You can either give the field name, or the fieldId, or indicate no field. In the last case, the system will automatically take the first main field.
- Be careful than if you change the name of the field in the tracker administration, the module parameter name will not be changed

See also

Module `last_modif_tracker_items`