

Overview

This page gives users further information on the Multi-like feature. This feature allows configurators to set multiple "like" options rather than just a simple "Like" button.

For a simple "Like" feature, you can make use of the PluginLike



Click to expand

FAQs

What does this Multi-Like feature do?

- The idea behind multi-like is to be able to expand on the like functionality to allow users to provide more qualitative feedback to the system.
- Rather than just allowing users to like/unlike things, multi-like allows users to select from a preset set of values. Multi-like also allows admins to provide numeric values to those selected options to provide a score for individual selections.
- Multi-value can be used on any Tiki object (article, forum, blog, trackeritem, etc)

Are there any limitations to this feature?

- Multi-like is not yet a mature feature and has its limitations. It works but hasn't been refined as of yet.
- Visually, it still needs some work to make it look good. It can be templated over though in themes as well.
- It also has yet to be incorporated into the core Tiki templates for forums, articles, blogs etc. The idea was to hold off on doing that until it's matured and we see if this is a feature that the community will want built-in.

Is it complicated to use? Are there any knowledge pre-requisites?

At this stage, Multi-like is not a particularly complicated feature but requires some knowledge of Smarty templates, Smarty functions, and how the Tiki file structure is set up to use properly.

Configuration

Multi-like configuration requires accessing the “Community” Control Panel with the “Advanced” feature on. Look for the preference titled "Configuration for multilike". *Note that every configuration must be separated by a blank line.*

Options	Description	Example
relation_prefix	This is the prefix used for the relation. Should be a two-part string, separated by a period and no spaces.	tiki.multilike1
ids	These are the ids for the various options. These are mandatory.	good,great,excellent
labels	These are the various labels for the options from which users can choose. These should be comma separated values	This was good,I thought this was great, Really excellent!
values	<i>(Optional)</i> You can set these to assign numerical values to the respective labels. These should be comma separated numbers, and the values count should equal the labels count.	1,3,5
allow_multi	<i>(Optional)</i> Sets whether you should be able to select multiple labels (like checkboxes). This should be set to 'y' if you want use 'checkbox' functionality. Otherwise it functions like radio buttons.	y (default: n)
icon_unselected	Since Tiki19, the name of the icon that will be use when no click has been recorded yet. By default it display a thumbs-up icon (outilned)	arrow-circle-up
icon_selected	Since Tiki19, the name of the icon that will be use when a click or more has been recorded. By default it display a thumbs-up icon (plain)	arrow-circle-down

Example value for configuration/preference field

```
relation_prefix=tiki.multilike1 ids=a,b,c values=1,3,5 labels=Good,Great,Excellent relation_prefix=tiki.multilike2  
ids=a,b,c labels=Creative,Interesting,Factual allow_multi=y
```

This would initialize two possible multi-like configurations that could be used (note the blank line between the two configurations; this is required).

- The first would be “radio button”-styled and would let users select from Good, Great, and Excellent
- The first would be checkbox-styled and would let users select from Creative, Interesting, and Factual

Permission configuration

Until better permission handling is developed for Relations, **tiki_p_post_comments** will be used to check permissions

Using a multi-like configuration in a Smarty template

Once multi-like is configured (see previous step), you may call it in a Smarty template using the "multilike" Smarty function. The parameters you must pass to this function are explained below:

Options	Description	Example
relation_prefix	This is the prefix used for the relation as defined in the configuration. Should be a two-part string, separated by a period and no spaces. (Required)	tiki.multilike1
type	This is the type of object that is being rated/liked. (Required)	article
object	This is the id of the object being liked. In most cases, you would likely assign a variable to this parameter. (Required)	\$articleId
onlyShowTotalPoints	If set to 'y' total number of points for object will be returned as an integer (Optional, 'n' by default)	onlyShowTotalPoints='y'
onlyShowTotalLikes	If set to 'y' total number of likes for object will be returned as an integer (Optional, 'n' by default)	onlyShowTotalLikes='y'
showOptionTotals	If set to 'y' each option will display their individual like counts next to label (Optional, 'n' by default)	showOptionTotals='y'
showPoints	Toggle the display of total points for object (Optional, 'n' by default)	showPoints='y'
showLikes	Toggle the display of likes for object (Optional, 'n' by default)	showLikes='y'
choiceLabel	Provide a custom label for choices (Optional, default label is 'I found this:')	choiceLabel='This article was:'
orientation	Set template orientation. Value can be either 'horizontal' or 'vertical'. (Optional, horizontal by default)	orientation='vertical'
showInPopup	Set whether the options should be contained in a popup (optional, 'n' by default)	showInPopup="n"
popupPlacement	Sets the placement of the popup (Optional, 'left' by default)	popupPlacement="top"

Example Smarty code to call a multi-like configuration

```
{multilike relation_prefix="tiki.multilike1" type="wiki page" object=$page}
```

Example of a like / unlike usage

In this case we want to set 2 multilike plugins, one for like and one for unlike, using different icons (added in Tiki19).

Note: since Tiki19 we upgrade to font Awesome 5 and there is still work to be complete about outlined icons

In the multilike parameters text area;

```
relation_prefix=tiki.multilike1 ids=a values=1 labels=like icon_selected=thumbs-up icon_unselected=thumbs-o-up
```

```
relation_prefix=tiki.multilike2 ids=a values=1 labels=don't like icon_selected=thumbs-down
```

```
icon_unselected=thumbs-o-down
```

In a module;

```
{multilike relation_prefix="tiki.multilike1" type="wiki page" object=$page showOptionTotals='y' showLikes='n'
choiceLabel=' '} {multilike relation_prefix="tiki.multilike2" type="wiki page" object=$page showOptionTotals='y'
showLikes='n' choiceLabel=' '}
```