

Plugin Mouseover

Introduced in Tiki3

Use this wiki plugin to display hidden content by mousing over text.

Parameters

Display hidden content by mousing over text

*Introduced in Tiki 3. Required parameters are in **bold**.*

[Go to the source code](#)

Preferences required: wikiplugin_mouseover

Parameters	Accepted Values	Description	Default	Since
(body of plugin)		Hidden content, unless the label parameter is undefined, in which case this is the label.		
<code>label</code>	text	Text displayed on the page. The body is the hidden content.		3.0
<code>url</code>	url	Destination link when mouseover text is clicked. Use http:// for external links	javascript:void(0)	3.0
<code>bgcolor</code>	text	Background color to apply to the popup		3.0
<code>class</code>	text	CSS class to apply	plugin-mouseover	4.0
<code>closeDelay</code>	digits	Number of seconds before popup closes	0	5.0
<code>effect</code>	(blank) none slide fade blind_ui clip_ui drop_ui explode_ui fold_ui puff_ui slide_ui	Set the type of show/hide animation that will be used		4.0
<code>height</code>	digits	Mouseover box height. Default: 200px	200	3.0
<code>offsetx</code>	int	Shifts the overlay to the right by the specified number of pixels relative to the cursor. Default: 5	5	3.0
<code>offsety</code>	int	Shifts the overlay lower by the specified number of pixels relative to the cursor. Default: 0	24	3.0
<code>padding</code>	digits	Padding size in pixels		3.0

tag	word	HTML tag to use for the label. Default <code>a</code>	a	9.2
text	text	DEPRECATED Hidden content. The body contains the label.		3.0
textcolor	text	Color to apply to the text in the popup		3.0
width	digits	Mouseover box width. Default: <code>400px</code>	400	3.0
speed	(blank) fast slow	Set the speed of the animation.		4.0
parse	(blank) y n	Parse the body of the plugin as wiki content (parsed by default)	y	3.0
parselabel	(blank) y n	Parse the label as wiki content (parsed by default)	y	5.0
sticky	(blank) y n	When enabled, popup stays visible until it is clicked.		3.0

Examples

Non-sticky Mouseover

This code:

```
{MOUSEOVER(label="Hello" offsetx="4" offsety="15")}Hello over there. It's fine!{MOUSEOVER}
```

Would produce:

Hello

Sticky Mouseover with TikiÃ¢ Syntax

This code:

```
{MOUSEOVER(label="Sticky" sticky="y" parse="y" offsetx="4" offsety="15")}This is a "sticky"  
popup{MOUSEOVER}
```

Would produce:
Sticky