

Plugin Fancy Table

Use this [wiki plugin](#) to display data using the odd/even table style. Settings allow the table to be sortable by multiple rows, cause rows to span multiple columns and vice versa, set individual column widths and align text horizontally and vertically. Beginning with [Tiki12](#) add sorting, filtering and pagination using the [tablesorter](#) parameters (separate tab below).

Parameters

Create a formatted table that can be filtered and sorted
Introduced in Tiki 1.
[Go to the source code](#)
Preferences required: wikipugin_fancytable

Parameters	Accepted Values	Description	Default	Since
(body of plugin)		Rows separated by >> in the header; for the table body, one row per line. Cells separated by (since Tiki4) or ~ ~ in both cases.		
tstotalformat		Format for table totals (click here for patterns). Example: #,###.		
colwidths		Column widths followed by "px" for pixels or "%" for percentages. Each column separated by .		4.1
headclass		CSS class to apply to the heading row.		1
head		Header rows of the table. Use >> to separate multiple rows.		1
class	text	Apply custom CSS class to customize the table design		27.2
colaligns	text	Table body column horizontal alignments, separated by . Choices: left, right, center, justify		4.1
colvaligns	text	Table body column vertical alignments, separated by . Choices: top, middle, bottom, baseline		4.1
desc	text	Table description.		27.3
headaligns	text	Horizontal alignments for header cells, separated by . Choices: left, right, center, justify		4.1

headvaligns	text	Vertical alignments for header cells, separated by ". Choices: top, middle, bottom, baseline		4.1
allowStickyHeaders	(blank) n y	Sticky Headers for the table when scrolling top value: No	n	26

Create a formatted table that can be filtered and sorted

[Go to the source code](#)

Parameters	Accepted Values	Description	Default	Since
sortable	any string except for HTML and PHP tags	Serves as the overall switch for turning jQuery Tablesorter on (also for filtering) as well as overall sort settings. Enter y to allow sorting and n to disallow (n is the default). Enter type:save to allow sorts to be saved between page refreshes. Enter type:reset;text:***** to allow sorting and show an unsort button with custom text. Enter type:savereset;text:buttontext to allow the same for saved sorts.	n	12.0
tsfilters	any string except for HTML and PHP tags	Enter y for a blank text filter on all columns, or n for no filters. Or set custom column filters separated by for each column for the following filter choices and parameters: Text - type:text;placeholder:xxxx (For PluginTrackerlist this will be an exact search, for other plugins partial values will work.) From Tiki 18, you can add initial:t option to allow prefix search for text filter. E.g. type:text;initial:t Dropdown - type:dropdown;placeholder:****;empty:****;option:****;option:****;option:**** Options generated automatically if not set and the server parameter is not y. Use value=Display label to have the option value be different than the displayed label in the dropdown. Use empty:Display label to include an option with the specified label that will filter only empty rows. Only used if other options are not specified manually. Date range - type:date;format:yy-mm-dd;from:2013-06-30;to:2020-12-31 (from and to values set defaults for these fields when user clicks on the input field)Beware that items with empty date values will not be shown when default date range filters are applied. Numeric range - type:range;from:0;to:50 No filter - type:nofilter For example: tsfilters="type:dropdown;placeholder:Type to filter..." would result in a dropdown filter on the first column with all unique values in that column in the dropdown list.		12.0
tscolselect	any string except for HTML and PHP tags	Add a button for hiding and re-showing columns. Also sets priority for dropping columns when browser is too narrow. Set each column to a number between 1 and 6 (1 is highest priority and last to be dropped) or to critical to never hide or drop. An example with 4 columns:tscolselect="critical 4 5 6"		14.0
tsfilteroptions	any string except for HTML and PHP tags	The following options are available: reset (adds button to take off filters), and hide (Filters are revealed upon mouseover. Hide doesn't work when date and range filters are used.). To use both, set tsfilteroptions="type:reset;text:button text;style:hide"		12.0
tsoutput	any string except for HTML and PHP tags	Enter y to set default values based on the site setting. Set custom values as in the following example: delivery:d;saveFileName:exported_teblesorter.csv		24.5
tspaginate	any string except for HTML and PHP tags	Enter y to set default values based on the site setting for maximum records in listings (on the pagination table of the Look & Feel admin panel). Set to n (and server cannot be set to y) for no pagination. Set custom values as in the following example: max:40;expand:60;expand:100;expand:140		12.0
sortList	any string except for HTML and PHP tags	Bracketed numbers for column number (first column = 0) and sort direction (0 = ascending, 1 = descending, n = no sort, y = allow sorting but no pre-sort), for example: 0,y,1,0,2,n. If the first pre-sorted or no filter column is not the first column, then you should use the y parameter (as in 0,y) to assign all previous columns.		12.0

tsortcolumns	any string except for HTML and PHP tags	Set type and group settings for each column, using to separate columns. To show group headings upon page load, the Pre-sorted Columns parameter (0sortList) will need to be set for a column with a group setting. Group will not work in plugins where the Server Side Processing parameter (server) is set to y. Set type to one of the following: text, digit, currency, percent, usLongDate, shortDate, isoDate, dateFormat-ddmmyyyy, ipAddress, url, time, nosort Also handle strings in numeric columns with: string-min, string-max Handle empty cells with: empty-top, empty-bottom, empty-zero. group creates automatic row headings upon sort with the heading text determined by the setting as follows: letter (first letter), word (first word), number, date, date-year, date-month, date-day, date-week, date-time. letter and word can be extended, e.g., word-2 shows the first 2 words. number-10 will group rows in blocks of ten. Group will not work in plugins where the Server Side Processing parameter (server) is set to y.	12.0
tstotaloptions	any string except for HTML and PHP tags	Pipe-separated options for totals for each column which are set in the tstotals parameter: format - overrides the default number format set in tstotalformat ignore - column will be excluded from total calculations set in the tstotals parameter. Remember to include any columns that will be added for row totals set in the tstotals parameter. Example: ignore ignore #,###.	15.0
tstotals	any string except for HTML and PHP tags	Generate table, column or row totals and set labels, using either y or the following syntax for each total: type:value;formula:value;filter:value;label:value. Setting to (y) will add one column total row set as follows: type:col;formula:sum;filter:visible;label:Totals. Separate multiple total row or column settings with a pipe (). Set type only to generate sums of visible values. In all cases, cells in columns set to be ignored in the tstotaloptions parameter will not be included in calculations. Instructions for each total option follows: type - Choices are col, for a row of columns totals, row, for a column of row totals, and all to include amounts from all cells in the table body in a row total. formula - set what the calculation is. Choices are: sum, count, max, min, mean, median, mode, range, varp, vars, stdevp, stdevs. Click here for a description of these options. filter - Determines the rows that will be included in the calculations (so no impact if type:row). Also, when server="y", only visible cells are included regardless of this setting. Choices are visible (rows visible on the page), unfiltered (all rows not filtered out, even if not visible because of pagination), all (all rows, even if filtered or hidden), and hidden (rows filtered out and rows hidden due to pagination). label - set the label for the total, which will appear in the header for row totals and in the first column for column totals.	15.0

Prerequisites and Tips

- In order to use tablesorter,
 - Javascript must be enabled (enabled by default at **Control Panels > Features > Programmer (tab)**)
 - jQuery Sortable Tables must be activated (at **Control Panels > Features > Interface (tab)**)
- Sorting a table with cells that span multiple columns or rows can give unexpected results
- Any | that you don't want interpreted as cell dividers may need to be placed inside of the ~np~ and ~/np~ tags, or using the ~|~ cell dividers may help.

Examples


Sorting, Filtering and Paginating

There are a number of options that allow the user to filter, sort and paginate a table. Below is an example that demonstrates many of these options.

This code:

```
{FANCYTABLE(head=" Fruit | Number | Vegetables | Date | Amount" sortable="type:reset" sortList="[0,0],[1,0]"
tsortcolumns="type:text;group:letter|type:digit;group:number|type:word;group:word|type:shortDate;group:date-
year|type:digit;group:number-10" tsfilters="type:text;placeholder:Type to
filter...|type:range;from:0;to:200|type:dropdown|type:date|type:range;from:5;to:60;style:popup" tsfilteroptions="type:reset"
tspaginate="max:5") } apples|10 | onions | 2/1/2010|40 lemons|200 | cucumbers | 3/3/2011|50 oranges|100 | carrots |
4/3/2012|60 lemons |10| tomatoes|1/2/2011|30 berries |50 | peas|6/6/2011|55 apples|10 | onions | 2/1/2010|66 lemons|200 |
cucumbers | 3/3/2011|66 oranges|100 | carrots | 4/3/2012|30 lemons |10| tomatoes|1/2/2011|22 berries |50 |
peas|6/6/2011|77 apples|10 | onions | 2/1/2010|77 lemons|200 | cucumbers | 3/3/2011|34 oranges|100 | carrots |
4/3/2012|56 lemons |10| tomatoes|1/2/2011|67 berries |50 | peas|6/6/2011|78 apples|10 | onions | 2/1/2010|89 lemons|200 |
cucumbers | 3/3/2011|12 oranges|100 | carrots | 4/3/2012|43 lemons |10| tomatoes|1/2/2011|32 berries |50 |
peas|6/6/2011|76 apples|10 | onions | 2/1/2010|76 lemons|200 | cucumbers | 3/3/2011|87 oranges|100 | carrots |
4/3/2012|11 lemons |10| tomatoes|1/2/2011|22 berries |50 | peas|6/6/2011|6 {FANCYTABLE}
```

Would produce:



Automatic Totals

Automatic columns, row and table totals can be added. In addition to sums, the totals can be the count, max, min, mean, median, mode, range, varp, vars, stdevp, and stdevs (click [here](#) for a description of these options). The number format can also be set to apply to all totals or specific formats for each. The example below has all three types of totals (column, row and table) as well as variations showing totals based on whether values are hidden or not, including due to filtering.

This code:

```
{FANCYTABLE(head=" Fruit | Number | Vegetables | Amount" sortable="type:reset" sortList="[0,0],[1,0],[2,y],[3,y],[4,n]"
colaligns="left|right|left|right" tsortcolumns="type:text|type:digit|type:word|type:digit"
tsfilters="type:text;placeholder:Type to
filter...|type:range;from:0;to:200|type:dropdown|type:range;from:5;to:60;style:popup" tsfilteroptions="type:reset"
tspaginate="max:5"
tstotals="type:col|type:col;filter:hidden|type:col;filter:all|type:all|type:all;filter:hidden|type:all;filter:all|type:row"
tstotaloptions="ignore||ignore|" tstotalformat="#,###.")} apples|10 | onions | 40 lemons|200 | cucumbers | 50 ... (leaving
out some rows for illustration) lemons |10| tomatoes|22 berries |50 | peas|6 {FANCYTABLE}
```

Would produce:

Multiple live filtering

In a simpler example, all you need to do is set `sortable` to `y`, in addition to being able to sort each column, you also get a line with fields to filter your data by matching a search string in one or more columns.

Example from <http://i18n.tiki.org/Status> :

This code:

```
{FANCYTABLE(head="Language code (ISO)|English name|Native Name|Completion|Percentage|Number of strings",
sortable="y")} ar | Arabic | العربية | {gauge value="2,29" size="100" showvalue="false"} | 2,29% | Total: 14923 %%%
Translated: 341 %%% Untranslated: 14582 bg | Bulgarian | български език | {gauge value="0,01" size="100"
showvalue="false"} | 0,01% | Total: 14922 %%% Translated: 2 %%% Untranslated: 14920 ca | Catalan | Català | {gauge
value="39,22" size="100" showvalue="false"} | 39,22% | Total: 14996 %%% Translated: 5882 %%% Untranslated: 9114 ...
{FANCYTABLE}
```

Would produce (upper part):

Reset Filter					
Language code (ISO)	English name	Native Name	Completion	Percentage	Number of strings
ar	Arabic	العربية		2,29%	Total: 14923 Translated: 341 Untranslated: 14582
bg	Bulgarian	български език		0,01%	Total: 14922 Translated: 2 Untranslated: 14920
ca	Catalan	Català		39,22%	Total: 14996 Translated: 5882 Untranslated: 9114

Click to expand

Then you can sort by one or more columns, and filter you results by searching for some string in one or more columns. In the example below, sorted by one column ("Percentage"), and filtered by content in another column ("Native name" containing "de"):

Reset Filter					
Language code (ISO)	English name	Native Name	Completion	Percentage	Number of strings
de	German	Deutsch		93,59%	Total: 14983 Translated: 14023 Untranslated: 960
nl	Dutch	Nederlands		21,06%	Total: 14964 Translated: 3152 Untranslated: 11812
fy-NL	Frisian Netherlands	Frysk Nederlâns		0,66%	Total: 14922 Translated: 98 Untranslated: 14824

Click to expand

Cells Spanning More Than One Row Or More Than One Col

If the cell begins with (multiple) \, then the cell spans (multiple) rows. Define lesser cols in the following rows.
If the cell begins with (multiple) /, then the cell spans (multiple) cols. Define lesser cols in this row.

This code:

```
{FANCYTABLE( head=" Col 1 | Col 2 ") } \1,1 (spans 2 rows)|1,2 2,2 //3,1 (spans 2 cols) {FANCYTABLE}
```

Would produce:

Col 1	Col 2
1,1 (spans 2 rows)	1,2
	2,2
3,1 (spans 2 cols)	

Related pages

- [PluginSplit](#) - arranges elements into an unformatted table
- [jQuery](#)
- [Tablesorter](#) - jQuery plugin used for sorting, filtering and pagination features
- <http://mottie.github.io/tablesorter/docs/> - documentation for the jQuery plugin used for the sorting, filtering and pagination features