

## Forums - Forum listing

Option	Description	Default
Default order		
Section order		
Topics		
Posts		
Posts per day (PPD)		
Last post		
Visits		
Description		
Description length		
Include category selector in forum list	Include a dropdown selector in the forum list to choose a category for the post.	
Forum post categories	Categories available in the category picker for forum posts.	

## Forums - General settings

Option	Description	Default
<a href="#">Forums</a>	Threaded or flat discussions.	
Home forum (main forum)		
Forum image file gallery	File gallery used to store images for forums	
Rankings	Users can see several charts or rankings about the page.	
Process inbound mail in cron job.	This prevent to process inbound mail when user is viewing a forum. This will require setting up a cron job running "php console.php forum:inbound-mail" command	
<a href="#">Accept wiki syntax</a>		
Strip wiki markup from outgoing forum emails	Convert outgoing emails from forum posts to plain text.	
Topic archiving		
Quick jumps		

Option	Description	Default
Replies are empty	<i>If disabled, replies will quote the original post</i>	
Allows quoting in flat forums	Allows users to reply.	
Don't display forum thread titles	Titles of posts usually don't change because they are a direct reply to the parent post. This feature turns off the display of titles in edit forms and forum display.	
Do not start messages titles with 'Re:'		
Require reply to have a title	Present an empty title input form and require it to be filled in before the forum post is submitted.	
First post of a thread can have an empty body	<i>Will be a thread title</i>	
Prevent Nesting of Quote wikipugins when replying	Strips quote plugin in reply in order to prevent nesting of quote plugins.	
Allow inbound email posts from anyone	Allow messages from non-users in the forums using incoming messages from any email address.	
Parse HTML in inbound email posts	Attempt to keep the formatting of HTML "rich text" emails if using WYSIWYG. <i>Experimental Has problems with some HTML emails, especially those with table-based layouts.</i>	
Uploaded filenames must match regex		
Send moderation email	Send email to forum moderators when post is queued	
Approve link in moderation email	Include a link for forum moderators to approve queue from email	
Manage thread defaults per-forum		
Display thread configuration bar	<i>Allows users to override the defaults</i>	
Keep settings for all forums during the user session		
Display the thread configuration bar only when the number of posts exceeds		
Number per page		
Default style		
Default sort mode		
Display forum thread or forum post title in the search engine friendly URL		
New email thread for each topic	If enabled each topic a forum will use it's own email thread, instead of all forum posts sharing the same one.	

Option	Description	Default
Forum name search	<i>When listing forums</i>	
Forum content search	<i>When listing forums</i>	
Topic content search		
Unified search for forums and file galleries		
Index posts on forum section change.	Re-indexes forum posts to match the parent section when the section is changed	

## Tags

Option	Description	Default
<a href="#">Tags</a>	Enables tags to be set on pages and other items for freeform categorization.	
<a href="#">Plugin Tagged</a>	List similarly tagged objects	
<a href="#">Plugin Add Tag</a>	Provide an input field for adding a tag to an object	
Show tag cloud	Show the full tag cloud in the list-tags screen.	
Maximum number of tags in cloud		
Show tags in middle column	On pages that have content tagged, this option enables the display of the tags at the top of those pages. Tags can be set, among other places, in the properties tab when editing a wiki page..	
Tag Suggestions	Number of tags to show in tag suggestions	
Valid characters pattern	Click on the links below to set or clear a pattern to limit characters accepted in tags. <i>Useful to eliminate characters such as “,” which users can enter by mistake instead of a space.</i>	
Lowercase tags only	Convert uppercase characters in tags to lowercase, if this is a preferred style for making tags more user-friendly..	
<a href="#">Multilingual tags</a>	Permits translation management of tags	
"More Like This" algorithm	enables tagged material to offer a find potentially related content. Basic will present content where a minimum number of tags match the item or page being viewed. Weighted is the same, but items are presented in Weighted (highest value first) sort order.	
Minimum number of tags in common	The minimum number of matching tags required for an item to be presented in the "More Like This" feature.	
Ordering of tagged objects	Default sort mode for tagged items	

Option	Description	Default
Preload random tag	A random tag will be selected on the tag search page (if no tag is pre-selected)..	

## Galleries - Features

Error: **Cant find gal-features** you may choose from one of the following:

- ads-activatethefeature
- ads-plugins
- ads-siteadsandbanners
- ads
- articles-articleslistingandview-articleview
- articles-articleslistingandview-listarticles
- articles-articleslistingandview
- articles-generalsettings-activatethefeature
- articles-generalsettings-features
- articles-generalsettings-plugins
- articles-generalsettings-sharingonsocialnetworks
- articles-generalsettings
- blogs-blogslistings-itemstodisplay
- blogs-blogslistings
- blogs-generalsettings-activatethefeature
- blogs-generalsettings-comments
- blogs-generalsettings-features
- blogs-generalsettings-plugins
- blogs-generalsettings-sharingonsocialnetworks
- blogs-generalsettings
- calendar-activatethefeature
- calendar-generalsettings
- calendar-plugins
- calendar
- category-activatethefeature
- category-categoryobjects
- category-features
- category-forum
- category-inlineplugins
- category-performance
- category-plugins
- category-poll
- category-structure
- category-theme
- category-tracker
- category-wiki
- category
- comments-annotations
- comments-displayoptions
- comments-sitewidefeatures
- comments-usingcommentsinvariousfeatures
- comments
- community-communityfeatures-additionalsoptions
- community-communityfeatures-community
- community-communityfeatures
- community-plugins
- community-socialinteraction-activitystream
- community-socialinteraction-friendshipandfollowers
- community-socialinteraction-goalrecognitionandrewards
- community-socialinteraction-score
- community-socialinteraction-selectwhichitemstodisplaywhenlistingusers

community-socialinteraction  
connect-jitsi-jitsi  
connect-jitsi  
connect-settings-tikiconnect  
connect-settings  
copyright-activatethefeature  
copyright-features  
copyright  
directory-activatethefeature  
directory-directory  
directory  
faqs-activatethefeature  
faqs-settings  
faqs  
features-globalfeatures-3  
features-globalfeatures-4  
features-globalfeatures-additionalfeatures  
features-globalfeatures-administrativefeatures  
features-globalfeatures-interactionwithonlineservicesorothersoftware  
features-globalfeatures-mailandsharing  
features-globalfeatures-mainfeatures  
features-globalfeatures-paymentandaccounting  
features-globalfeatures-progressivewebapp  
features-globalfeatures-secondaryfeatures  
features-globalfeatures  
features-interface-elementplus  
features-interface-experimental  
features-interface-jquerypluginsandaddons  
features-interface  
features-programmer-customcode  
features-programmer-loggingandreporting  
features-programmer  
fgal-adminlistings-0  
fgal-adminlistings  
fgal-enhancements-access  
fgal-enhancements-draw  
fgal-enhancements-h5p  
fgal-enhancements-scorm  
fgal-enhancements-vimeo  
fgal-enhancements  
fgal-generalsettings-activatethefeature  
fgal-generalsettings-features  
fgal-generalsettings-quota  
fgal-generalsettings-settingsfordiagrams  
fgal-generalsettings-settingsformediaalchemyst  
fgal-generalsettings-settingsforrecordrtc  
fgal-generalsettings-uploadregex  
fgal-generalsettings  
fgal-listings  
fgal-plugins-plugins  
fgal-plugins  
fgal-searchindexing  
forums-forumlisting  
forums-generalsettings-activatethefeature  
forums-generalsettings-features  
forums-generalsettings-searches  
forums-generalsettings-threads  
forums-generalsettings  
freetags-activatethefeature  
freetags-plugins  
freetags-tags  
freetags-tagsearchpage  
freetags  
general-dateandtime-datetimeselectors  
general-dateandtime-timezoneandformat

general-dateandtime  
general-generalpreferences-errortracking  
general-generalpreferences-headlessbrowserintegration  
general-generalpreferences-loggingandreporting  
general-generalpreferences-mail  
general-generalpreferences-newsletter  
general-generalpreferences-schedulersettings  
general-generalpreferences-siteidentity  
general-generalpreferences-webcron  
general-generalpreferences  
general-generalsettings-contact  
general-generalsettings-help  
general-generalsettings-multidomain  
general-generalsettings-server  
general-generalsettings-sessions  
general-generalsettings-siteterminal  
general-generalsettings-stats  
general-generalsettings-termsandconditions  
general-generalsettings  
general-navigation-breadcrumbs  
general-navigation-homepage  
general-navigation-menus  
general-navigation-namespace  
general-navigation-redirects  
general-navigation-siteaccess  
general-navigation-sitemapprotocol  
general-navigation-user  
general-navigation  
i18n  
intertiki-intertikiclient-activatethefeature  
intertiki-intertikiclient-clientserversettings  
intertiki-intertikiclient-currentlylinkedmasterserver  
intertiki-intertikiclient  
intertiki-intertikimasterserver-activatethefeature  
intertiki-intertikimasterserver-masterserversettings  
intertiki-intertikimasterserver  
login-cas-cascentralauthenticationservice  
login-cas-casserver  
login-cas  
login-generalpreferences-captcha  
login-generalpreferences-cookies  
login-generalpreferences-password  
login-generalpreferences-registration  
login-generalpreferences-username  
login-generalpreferences  
login-ldap-ldapadmin  
login-ldap-ldapbindsettings  
login-ldap-ldapuser  
login-ldap-warning  
login-ldap  
login-ldapexternalgroups-ldapadmin  
login-ldapexternalgroups-ldapbindsettings  
login-ldapexternalgroups-ldapexternalgroups  
login-ldapexternalgroups-ldapgroup  
login-ldapexternalgroups-ldapgroupmemberifgroupmembershipcanbefoundingroupattributes  
login-ldapexternalgroups-ldapuser  
login-ldapexternalgroups-ldapusergroupifgroupmembershipcanbefoundinuserattributes  
login-ldapexternalgroups  
login-oauthserversettings-0  
login-oauthserversettings  
login-openidconnect-0  
login-openidconnect  
login-pam-pam  
login-pam  
login-passwordblacklist-password

login-passwordblacklist  
login-phpbb-phpbb  
login-phpbb  
login-remotetikiautologin-warning  
login-remotetikiautologin  
login-saml2-advancedsettings  
login-saml2-attributemapping  
login-saml2-groupmapping  
login-saml2-identityprovidersettings  
login-saml2-options  
login-saml2-saml2  
login-saml2  
login-shibboleth-shibboleth  
login-shibboleth  
login-webserver-webserver  
login-webserver  
look-customization-customcode  
look-customization-editing  
look-customization  
look-layout-logo  
look-layout-modulezonevisibility  
look-layout-sitereportbar  
look-layout-title  
look-layout  
look-miscellaneous-contextmenus  
look-miscellaneous-favicons  
look-miscellaneous-responsiveimages  
look-miscellaneous-separators  
look-miscellaneous-tabs  
look-miscellaneous  
look-pagination  
look-shadowlayer  
look-theme  
look-uieffects-other  
look-uieffects-standarduieffects  
look-uieffects-tabuieffects  
look-uieffects  
maps-defaults  
maps-settings  
maps  
mautic-credentials  
mautic-mainsettings  
mautic  
messages-activatethefeature  
messages-settings  
messages  
metatags-geomatags  
metatags-metatags-facebook  
metatags-metatags-general  
metatags-metatags-twitter  
metatags-metatags  
metatags-robots  
module-crumbscrumbdescription  
module-modulezonevisibility  
module  
payment-advancedshoppingcart-advancedcarttrackernamessetup  
payment-advancedshoppingcart-cartsettings  
payment-advancedshoppingcart-features  
payment-advancedshoppingcart-producttrackerssetup  
payment-advancedshoppingcart  
payment-payment-0  
payment-payment  
payment-plugins-plugins  
payment-plugins  
payment-shipping

performance-database  
performance-majorslowdown  
performance-memcache  
performance-monitor  
performance-newsletter  
performance-performance  
performance-plugins  
performance-redis  
performance-sessions  
performance-timeandmemorylimits  
performance-wiki  
polls-polls-activatethefeature  
polls-polls-plugins  
polls-polls-settings  
polls-polls  
polls-surveys-1  
polls-surveys-activatethefeature  
polls-surveys  
print-articles  
print-otherfeatures  
print-pdfsettings  
print-wikiprintversion  
print  
profiles-advanced-repositorystatus  
profiles-advanced  
rating-advanced  
rating-articles  
rating-comments  
rating-defaultoptions  
rating-globalconfiguration  
rating-trackers  
rating-userinterface  
rating-wiki  
rating  
rss-feeds  
rss-generalpreferences  
rss-incomingfeeds  
rtc-bigbluebutton  
rtc-xmpp  
score-activatethefeature  
score-causescoresolderthanacertainnumberofdaystoexpire  
score  
search-federatedsearch  
search-generalsettings-features  
search-generalsettings-filegalleriessearches  
search-generalsettings-forumsearches  
search-generalsettings-search  
search-generalsettings  
search-searchresults-informationtodisplayforeachresult  
search-searchresults-itemstodisplayinsearchresults  
search-searchresults  
search-storedsearch  
security-api  
security-generalsecurity-csrfsecurity  
security-generalsecurity-httpheaders  
security-generalsecurity-smartyandfeaturessecurity  
security-generalsecurity-trackerssecurity  
security-generalsecurity-userencryption  
security-generalsecurity  
security-openpgp-openpgpfunctionalityforpgpmimeencryptedemailmessaging  
security-openpgp  
security-siteaccess  
security-spamprotection-captcha  
security-spamprotection  
security-tokens



security-webhooks  
sefurl-activatethefeature  
sefurl-settings  
sefurl  
semantic-activatethefeature  
semantic  
share-activatethefeature  
share-sitewidefeatures  
share  
socialnetworks-bit  
socialnetworks-general  
socialnetworks-legacyintegrations-facebook  
socialnetworks-legacyintegrations-linkedin  
socialnetworks-legacyintegrations-warning  
socialnetworks-legacyintegrations  
socialnetworks-sharethis  
stats-googleanalytics-0  
stats-googleanalytics  
stats-piwikanalytics-0  
stats-piwikanalytics  
stats-tikistatistics-0  
stats-tikistatistics  
textarea-generalsettings-defaultsize  
textarea-generalsettings-externallinksandimages  
textarea-generalsettings-features  
textarea-generalsettings-markdown  
textarea-generalsettings-miscellaneous  
textarea-generalsettings-plugins  
textarea-generalsettings-typography  
textarea-generalsettings-wikisyntax  
textarea-generalsettings  
textarea-plugins-editpluginicons  
textarea-plugins-filter  
textarea-plugins-pluginpreferences  
textarea-plugins-plugins  
textarea-plugins  
trackers-plugins-0  
trackers-plugins  
trackers-settings-activatethefeature  
trackers-settings-fieldsettings  
trackers-settings-linkedwikipages  
trackers-settings-trackerattachmentpreferences  
trackers-settings-trackerforcefillfeature  
trackers-settings-trackersettings  
trackers-settings  
trackers-systemtrackers-systemtrackers  
trackers-systemtrackers  
user-messagingandnotifications-messages  
user-messagingandnotifications-usernotifications  
user-messagingandnotifications  
user-userfeatures-useraccountfeatures  
user-userfeatures  
user-userfiles-activatethefeature  
user-userfiles-settings  
user-userfiles  
user-userinfoandpicture-profilepicture  
user-userinfoandpicture-userinformationdisplay  
user-userinfoandpicture  
user-usersettings-adminuserpreferences  
user-usersettings-defaultuserpreferences  
user-usersettings  
video-kaltura-activatethefeature  
video-kaltura-enablerelatedtrackerfieldtypes  
video-kaltura-kalturadynamicplayer  
video-kaltura-kalturapartnersettings

video-kaltura-kaltratikiconfig  
video-kaltura-legacysupport  
video-kaltura-plugintoembedinpages  
video-kaltura  
webservices-activatethefeature  
webservices-options  
webservices  
wiki-features-attachments  
wiki-features-comments  
wiki-features-generalfeatures  
wiki-features-namespaces  
wiki-features-redirectandsimilar  
wiki-features-structures  
wiki-features-wikiwatch  
wiki-features-wikiwordsfeatures  
wiki-features  
wiki-flaggedrevision-0  
wiki-flaggedrevision  
wiki-generalpreferences-activatethefeature  
wiki-generalpreferences-automatictableofcontents  
wiki-generalpreferences-editing  
wiki-generalpreferences-pagedisplay  
wiki-generalpreferences-pagename  
wiki-generalpreferences-plugins  
wiki-generalpreferences  
wiki-pagelistings-configuration  
wiki-pagelistings-options  
wiki-pagelistings  
workspace-areas-activatethefeature  
workspace-areas  
workspace-workspaces-activatethefeature  
workspace-workspaces-advanced  
workspace-workspaces-dependencies  
workspace-workspaces  
wysiwyg-activatethefeature  
wysiwyg-legacyckeditorwysiwyg  
wysiwyg-markdowntoastuiwysiwyg  
wysiwyg-relatedfeatures  
wysiwyg-wysiwygeditorfeatures  
wysiwyg

## General - Date and time

Option	Description	Default
Time zone	Indicates the default time zone to use for the server.	
Displayed time zone	Use time zone set from user preferences, or the automatically detected time zone for anonymous (if browser allows). Site default is used as fallback.	
<a href="#">Long date format</a>	Specify how Tiki displays the date (longer version)	
<a href="#">Short date format</a>	Specify how Tiki displays the date (shorter version)	
<a href="#">Long time format</a>	Specify how Tiki displays the time (longer version)	
<a href="#">Short time format</a>	Specify how Tiki displays the time (shorter version)	

Option	Description	Default
<a href="#">Short JavaScript date format</a>	Used in the date picker fields	
<a href="#">Short JavaScript time format</a>	Used in the datetime picker fields	
Fields display order	The order date field inputs should be listed in.	
Start year	Year to show first in dropdown lists. For example, use "-2" for the current year minus two, or "2010" for a specific year	
End year	Year to show last on dropdown lists. For example, use "+2" for the current year plus two, or "2016" for a specific year	
<a href="#">Select month in Date Picker</a>	Users can select month in the Date Picker instead of seeing month as text.	
<a href="#">Select year in Date Picker</a>	Users can select year in the Date Picker instead of seeing year as text.	
Use 12-hour clock for time selectors	Use the 12-hour clock (with AM and PM) in some edit screens to set the time for publishing new or edited blog posts, articles, etc.	
Skip date for same day	When displaying short date and time, skip date for today. Only time will be displayed.	
jQuery Timeago	jQuery plugin for fuzzy timestamps.	
<a href="#">Plugin Now</a>	Show the current date and time	
<a href="#">Plugin Countdown</a>	Display the time until or after a date and time	
<a href="#">Plugin Convene</a>	Suggest meeting dates and times and vote to select one	

## General - General preferences

Option	Description	Default
Server domain name	The value that will be used by default as the server domain name of your Tiki site. <i>Leave this blank if you are not entirely sure what you are doing. If this value is incorrect or your DNS is not set up properly it will lock you out of your Tiki and require database or shell access to recover it.</i>	
Browser title	Visible label in the browser's title bar on all pages. Also appears in search engine results.	
Fallback for tiki base URL	The full URL to the Tiki base URL including protocol, domain and path (example: <a href="https://example.com/tiki/">https://example.com/tiki/</a> ), used when the current URL can not be determined, example, when executing from the command line.	
Browser title position	Position of the browser title in the full browser bar relative to the current page's descriptor.	

Option	Description	Default
Browser title display mode	When breadcrumbs are used, method to display the browser title.	
Sender email	Email address that will be used as the sender for outgoing emails.	
Sender full name	Real name that will be used as the sender for outgoing emails	
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
Email newline character(s)	End-of-line (EOL) character used in outgoing emails	
Apply site styles to HTML emails	Add site CSS to all HTML formatted emails	
Mail sender	Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at ./temp/Mail_yyyymmddhhmmss_randomstring.tmp ) to send mail notifications.	
Amazon SES Key		
Amazon SES Secret		
Amazon SES Region		
Amazon SES version		
Elastic Email Username		
Elastic Email Key		
Mailgun Domain		
Mailgun Key		
Mailgun API Endpoint		
Mandrill Key		
Postage Key		
Postmark Key		
SendGrid Username		
SendGrid Key		
SparkPost Key		
SMTP server		
Authentication	Mail server authentication	

Option	Description	Default
Username		
Password		
Port		
Security		
Verify HTTPS certificates of remote servers	When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)	
Local server name	Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.	
Mail delivery	When set to Queue, messages will be stored in the database. Requires using the shell script <code>php console.php mail-queue:send</code> to be run for actual delivery.	
Catch-all email address	Tiki will send all emails to this email address instead of the target recipients. This will actually rewrite the recipient TO, CC and BCC email headers.	
Email footer	Text appended to outgoing emails.	
Text string used to customise mail templates	Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files	
Throttle newsletter send rate	Pause for a given amount of seconds before each batch to avoid overloading the mail server.	
Newsletter pause length	Number of seconds delay before each batch	
Newsletter batch size	Number of emails to send in each batch	
Allow sending newsletters through external clients	Generate mailto links using the recipients as the BCC list. <i>This will expose the list if email addresses to all users allowed to send newsletters.</i>	
PHP Error reporting level	Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.	
PHP errors visible to admin only	PHP Errors will be shown to only the Admin user. <i>During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.</i>	
Include Smarty notices in the PHP error report	Tiki will display <a href="#">Smarty</a> notices with the PHP error messages. <i>In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.</i>	
Show generic error message	Show a generic error message for non admins users. The error is logged to the database.	
Generic error message	Message to display to non admin users when an error occurs.	

Option	Description	Default
<a href="#">Log mail in Tiki logs</a>	A line of type mail will be included in the System Log with the destination address and subject of each email sent. <i>May impact performance</i>	
Log SQL	All SQL queries will be registered in the database in the tiki_sql_query_logs table. <i>Do not enable this feature all the time. It can be very resource intensive and will impact performance.</i>	
Log queries using more than	Use to log only queries that exceed a specific amount of time. <i>May impact performance</i>	
Data Source Name (DSN)	DSN used for connect to the error tracking service.	
Sample rate	Sampling allows you to better manage the number of reported events, so you can tailor the volume of data needed. Use a value between 0 and 1. E.g.: 0.25 (will report 25% of the events)	
Track PHP errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for PHP.	
Track JavaScript errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for JavaScript.	
<a href="#">Enabled</a>	Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.	
How to trigger Web Cron		
Run interval	The amount of time of each run	
Token	The token to use when running the cron manually	
<a href="#">Scheduler</a>	Provides the ability to run tasks at a scheduled time.	
Delay scheduled time (minutes)	When calculating if the jobs should run, take the delay into consideration	
Allow shell command execution	Give the possibility to execute shell commands.	
Scheduler stalled after (minutes)	Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.	
Notify on stalled schedulers	Send an email notification when a stalled scheduler is detected.	
Users to notify on stalled task	List of users/emails separated by comma to be notified when a scheduler task is set to stalled.Ex: admin,operations@example.com <b>If empty, the email will be sent to all administrators.</b>	
Self healing after (minutes)	Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing	
Notify on healed schedulers	Send an email notification when a stalled scheduler is healed.	

Option	Description	Default
Users to notify on healed task	List of users/emails separated by comma to be notified when a scheduler task is set to healed.Ex: admin,operations@example.com <b>If empty, the email will be sent to all administrators.</b>	
Number of logs to keep	0 will keep all logs	
Headless Browser Integration Type	Type of headless browser integration to be used.	
Chrome Binary Path	This ensures that the ChromePHP library can locate and execute the Chrome browser for headless operations	

## General - General settings

Option	Description	Default
Temporary directory	Directory on your server, relative to your Tiki installation, for storing temporary files. Tiki must have full read and write access to this directory.	
Use proxy	Specify if this Tiki site requires a proxy to access the internet. If enabled, the proxy Host name (either with or without the http:// prefix), Port settings, Username, and Password can be specified.	
Proxy host name	Proxy host - without http:// or similar, just the host name	
Port	Proxy port	
Proxy username		
Proxy password		
HTTP lookup: skip framesets	When performing an HTTP request to an external source, verify if the result is a frameset and use heuristic to provide the real content.	
Load balancer	Activate this only if the server is behind a load balancer (or reverse proxy). This enables logging the IP of the user rather than the IP of the proxy server	
Tiki is behind a frontend-proxy/load-balancer that rewrites ports	Activate this only if the server is behind a frontend-proxy/load-balancer (or reverse proxy) that rewrites ports. This enables Tiki to use the HTTP_X_FORWARDED_PROTO parameter set by the proxy, to provide correct links.	
Access-Control-Allow-Origin	Domains allowed to make "CORS" (Cross-Origin Resource Sharing or Cross-Domain Ajax) requests from this server. <i>One URI per line, for example, "http://www.example.com" or "*" for any site</i>	
Use CURL for HTTP connections	Use CURL instead of sockets for server to server HTTP connections, when sockets are not available.	

Option	Description	Default
<a href="#">Realtime Tiki</a>	Use built-in websockets server within Tiki to enable realtime communication features of the app. See help page for more information on how to start the server.	
Realtime port	The port used to access this server; if not specified, port 8080 will be used <i>If not specified, port 8080 will be used</i>	
Path to the php binary	Path to the php command line binary to be used by tiki when calling command line programs	
<a href="#">Multi-domain</a>	Enable domain names to be mapped to perspectives and simulate multiple domains hosted with the same Tiki installation.	
Switch domain when switching perspective	Important: Different domains have different login sessions and, even in the case of subdomains, an understanding of session cookies is needed to make it work	
Default domain for non categorized content	The domain (hostname only) to be used when redirecting the user if he tries to read content that is not bound to the category/perspective configured for the current domain.	
Multi-domain Configuration	Comma-separated values mapping the domain name to the perspective ID. <i>One domain per line with a comma separating it from the perspective ID. For example: tiki.org,1</i>	
Session storage location	Select where the session information should be stored. Memcache sessions require memcache to be configured.	
Session lifetime	Session lifetime <i>Expressed as minutes. This is the minimum time logged in. To be the exact time, adjustments must be made in .htaccess session.gc_probability and session.gc_divisor to 1. Be careful - changing the probability may affect server performance.</i>	
Session cookie name	Session cookie name used instead of the PHP default configuration	
Site terminal	Allows users to be directed to a specific perspective depending on the origin IP address. Can be used inside intranets to use different configurations for users depending on their departements or discriminate people in web contexts. Unspecified IPs will fall back to default behavior, including multi-domain handling. Manually selected perspectives take precedence over this.	
Site terminal configuration	Provides the mapping from subnets to perspective. <i>One per line. Network prefix in CIDR notation (address/mask size), separated by comma with the perspective ID. Example: 192.168.12.0/24,12</i>	
<a href="#">Contact us</a>	A basic contact form a visitor can use to contact the site admin <i>You can use Trackers to create custom Contact Us forms.</i>	
<a href="#">Allow anonymous visitors to use the "Contact Us" feature.</a>	Allow anonymous visitors to use the "Contact Us" feature.	



Option	Description	Default
<a href="#">Display contact priority</a>	Display contact priority option	
Contact user	User to contact	
<a href="#">Stats</a>	Record basic statistics about major Tiki features (number of wiki pages, size of file galleries, etc.)	
<a href="#">Referrer stats</a>	Record domain name of sites that send visitors to this Tiki.	
Count admin pageviews	Include pageviews by Admin when reporting stats.	
<a href="#">Terms and Conditions</a>	Automatically present a terms of use page to be accepted by users accessing the site.	
Terms of Use page name	Wiki page for Terms of Use content. The page may be translated using the multilingual feature.	
Minimum age	When presenting the terms of use, request age. <i>0 to ignore age validation</i>	
<a href="#">Help system</a>	Activates links to Tiki documentation. You can specify a Help URL that contains customized help pages. By default, the Help system uses <a href="http://doc.tiki.org/">http://doc.tiki.org/</a>	
<a href="#">Help URL</a>	The default help system may not be complete. You can contribute to the Tiki documentation, which is a community-edited wiki.	

## General - Navigation

Option	Description	Default
SmartMenus	Add "SmartMenus" to Bootstrap menus. See smartmenus.org for more.	
<a href="#">Menu user levels</a>	Enables control of the per-group visibility of menu options	
<a href="#">Featured links</a>	A simple menu system to display external web pages in a new browser tab or an iframe within the site, etc.	
Use folder icons for menu section (parent) items	When a menu isn't set as a Bootstrap or CSS menu, use folder icons for menu section items (rather than plus/minus signs).	
Menu icons	Allows icons to be defined for menu entries	
Default path for the icons		
Edit menu icon	Adds an icon on the navbar to edit menu entries	
<a href="#">Use group homepages</a>	Users can be directed to different pages upon logging in, depending on their default group.	

Option	Description	Default
Go to the group homepage only if logging in from the default homepage		
Use the top page of a Tiki feature as the homepage	Select the Tiki feature to provide the site homepage. Only enabled features are listed.	
Use custom homepage	Use the top page of a Tiki feature or another homepage <i>This option will override the Use Tiki feature as homepage setting.</i>	
Homepage URL		
Homepage Browser title	Customize Browser title for the custom homepage	
Wiki homepage	The default home page of the wiki when no other page is specified. The page will be created if it does not already exist.	
Home blog (main blog)		
Home forum (main forum)		
Home file gallery (main file gallery)	Select the default file gallery	
Domain prefix handling	Strip or automatically add the "www." prefix on domain names to standardize URLs.	
Domain redirects	When the site is accessed through specific domain names, redirect to an alternate domain preserving the URL. Useful for domain name transitions, like tikiwiki.org to tiki.org. <i>One entry per line, with each entry a comma-separated list: old domain, new domain</i>	
<a href="#">Redirect on error</a>	On an error, refresh to the homepage as specified on the Admin General page.	
<a href="#">Redirect to similar wiki page</a>	If a requested page doesn't exist, redirect to a similarly named page	
On permission denied, display login module	If an anonymous visitor attempts to access a page for which permission is not granted, Tiki will automatically display the Log-in module. Alternatively, use the Send to URL field to display a specific page (relative to your Tiki installation) instead.	
Send to URL	URL to redirect to on "permission denied"	
The URL that the anonymous user is redirected to when a page is not found		
URL the user is redirected to after account validation	The default page a Registered user sees after account validation is "tiki-information.php?msg=Account validated successfully". <i>Default: tiki-information.php?msg=Account validated successfully.</i>	
Alternate registration page	Enter URL of a custom registration page. Tiki will automatically redirect default registration page (tiki-register.php) to this page.	

Option	Description	Default
<a href="#">URL Suffix Cleaner</a>	When the requested page does not exist, tests removing 1 or 2 of the last characters from the URL to see if it gets an existing page.	
URL to go to when clicking on a username	URL to go to when clicking on a username. Default: tiki-user_information.php?userId= <i>(Use for login name and No value assigned for userId)</i>	
<a href="#">Sitemap protocol</a>	Allows generating site maps based on the Sitemap protocol, in the form of XML documents. Mostly used to facilitate indexation of a site by web search engines.	
<a href="#">Close site</a>	Use this setting to "close" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site.	
Title		
Message		
<a href="#">Close site when server load is above the threshold</a>	Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site.	
Maximum average server load threshold in the last minute		
Site Busy Title		
Site Busy Message		
<a href="#">Breadcrumbs</a>	Indicates the navigation path through parent pages to the current page. <i>Unmaintained feature</i>	
Prefix breadcrumbs with "Location : "	Place the term "Location:" in the breadcrumbs.	
Site location bar		
Larger font		
Use page description		
<a href="#">Namespace</a>	Enable namespaces feature for wiki pages.	
Namespace separator	Select the character, symbol, or text to use as the namespace separator.	
Hide namespace indicator in structure path	Hide namespace indicator in structure path.	
Center text using : instead of	<i>Useful to avoid conflicts with C++ scope operators or default namespace separator</i>	

Option	Description	Default
Page name display stripper	The character(s) to use as a delimiter in the page name. The portion of the name after the character(s) will not be displayed. If the page name display stripper conflicts with the namespace separator, the namespace is used and the page name display is not stripped.	

## Internationalization (i18n)

Option	Description	Default
<a href="#">Default language</a>	The site language is used when no other language is specified by the user.	
<a href="#">Default admin language</a>	The site language is used in admin section when no other language is specified by the user.	
Wiki link format	Level of special characters acceptable in wiki links for page names. For example: Page éâî <i>"Strict" includes only basic characters such as a-z and 0-9. A site that uses accented or special characters in page names should not use "strict".</i>	
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
<a href="#">Multilingual</a>	Enables internationalization features and multilingual support at the site.	
Detect browser language	Look up the user's preferred language through browser preferences.	
Show pages in user's preferred language	When accessing a page which has an equivalent in the user's preferred language, favor the translated page. Based on the user's Tiki preferences.	
Users can choose the language of their interface	Allow users to change the language of the menus and labels.	
Restrict supported languages	Limit the languages made available on the site. <i>Use Ctrl+Click to select multiple languages.</i>	
Available languages	By default, all languages supported by Tiki are available on multilingual sites. This option allows limiting the languages to a subset.	
<a href="#">Language inclusion threshold</a>	When the number of languages is restricted on the site, and is below this number, all languages will be added to the preferred language list, even if unspecified by the user. However, priority will be given to the specified languages.	
Display available translations	Display list of available languages and offer to switch languages or translate. This appears on wiki pages and articles action buttons.	
Display available translations as dropdown	Instead of a simple icon to list available languages or translation options, show a more visible drop-down list.	

Option	Description	Default
Synchronize page and site language	Changing the page language also changes the site language	
Restrict search language by default	Only search content that is in the interface language, otherwise show the language menu.	
<a href="#">Translation assistant</a>	Track translation operations between pages.	
Urgent translation notifications	Enable changes to be flagged as urgent, so translations are marked with a notice visible to all users.	
Incomplete translation notice	When a page is translated to a new language, a notice will automatically be inserted into the page to indicate that the translation is not yet complete.	
Display all languages in a single page	List all languages as options in the page-language dropdown list, to see them all at once.	
Quantify change size	In addition to tracking the changes, track the change size and display approximately how up-to-date the page is.	
Allow minor edits of wiki pages	Minor edits don't flag new content for translation and don't cause watch notifications to be sent (unless "Watch minor edits" is enabled).	
<a href="#">User watches translations</a>		
Multilingual structures	Structures search for equivalent pages in other languages. <i>May cause performance problems with larger structures.</i>	
<a href="#">Multilingual tags</a>	Permits translation management of tags	
Synchronize multilingual categories	Make sure that the categories of the translations are synchronized when modified on any version.	
Synchronized categories	List of categories affected by the multilingual synchronization. Depending on the parent feature, this list will be used as a white list (the only categories allowed) or as a black list (all categories allowed except those specified).	
Multilingual dynamic variables	Make dynamic variable content language-specific.	
<a href="#">Plugin Translate</a>	Translate text to the user language	
<a href="#">Plugin Language</a>	Show alternative content based on the page language	
<a href="#">Plugin Translated</a>	Create multilingual links	
<a href="#">Use database for translation</a>	Use the database to store the translated strings and allow using interactive translation <i>Edit, export and import languages</i>	
Manage contribution of translated strings	Offers to set whether each translated string should be contributed to the Tiki community or kept locally	
Record untranslated strings	Keep track of the unsuccessful attempts to translate strings.	

Option	Description	Default
<a href="#">Machine translation</a>	Uses machine translation to translate the content of the site to other languages. Note that this feature relies on external services that may not be free. Google Translate is a paid service.	
Machine translation implementation	Select between alternate implementations for machine translation. Depending on the implementation, different API keys may be required.	
Google Translate API Key	The key must be generated from the Google console. Choose to create a server key.	
Bing Translate Client ID	The application must be registered.	
Bing Translate Client Secret	The application must be registered.	
Enable machine translation of wiki pages	Makes additional languages available to the list of languages on the page.	
Certain pages redirect to homepage when language is changed		
List of pages that redirect	List of names of pages that always redirect to the homepage when the language is switched <i>Separate page names by commas</i>	

## Intertiki - Client

Option	Description	Default
<a href="#">Intertiki</a>	Allows several Tiki sites (slaves) to get authentication from a master Tiki site	
Client key for this site	This must match the shared key entered in the Master's key field.	
Intertiki shared cookie	Causes a user who logs into or out of either the slave or master site to be automatically logged into or out of all other sites. <i>The remember me login feature must be on.</i>	
Master Tiki server	Master Tiki server that this client will obtain user authorizations from. <i>Overrides manually registered local users</i>	
Import user preferences	Client Tiki will copy the user preferences from the master server. <i>This will overwrite local user preferences every time the user logs in.</i>	
Import user groups	Groups the user belongs to on the master server will be imported (along with their security definitions). <i>This will overwrite local groups every time a user logs in.</i>	
Limit group import	This list will limit the group import feature to only those groups listed here. <i>Comma-separated list of case-sensitive imported groups. Leave empty to avoid limitation.</i>	

## Intertiki - Master server

Option	Description	Default
This site is a master server		
Access log file	location, from your tiki root dir, where you want the access log file stored.	
Errors log file	location, from your tiki root dir, where you want the error log file stored	